



TRANSMISSIONS



Mechanical Power Transmission

Dunlop BTL Ltd

European Distribution Centre
MPT House
Brunswick Road
Cobbs Wood Industrial Estate
Ashford, Kent. UK
TN23 1EL

Contact us

-  +44 (0)1233 663340
-  +44 (0)1233 664440
-  sales@dunlopbtll.com
-  www.dunlopbtll.com

Manufacturing Facilities

UNITED KINGDOM

FRANCE

GERMANY

ITALY

SPAIN

POLAND

CZECH REPUBLIC

SLOVAKIA

SERBIA

CHINA

USA





V-BELT LINK BELTING

Description

V-belt Link belting offers a fast alternative to a V-Belt or Wedge Belt in an emergency break down situation, due to the ease in which the belts length can be adjusted to suit any application.

Also used as preferred belting product in applications where an endless belt can not be fitted without an expensive machine breakdown as it can be threaded into place and connected in situ without the need for shafts and bearings to be dismantled.



Part No.	Belt width (mm)	Belt Depth (mm)	V-Belt Section
Z-Link Twist Belt	10	6	Z
A-Link Twist Belt	13	8	A
B-Link Twist Belt	17	11	B
C-Link Twist Belt	22	14	C

DUNLOP V-Belt Link Belting is the ideal replacement substitute for conventional rubber V-Belts and offers a permanent or ideal temporary replacement for conventional rubber V-Belts. Dunlop V-Belt Link Belting combines superior strength, durability and quick, easy assembly to keep equipment up and running at the same running horse power ratings as rubber belts.

- Durable urethane coating precision machined sides for smooth engagement
- Rugged, woven polyester fabric for strength and longer belt life
- Dunlop urethane construction offers superior resistance to most common industrial solvents and chemicals, oil, water and extreme temperatures, from -25°C to 80°C
- Dissipates heat so they run cooler than conventional belts

INSTALLATION

Installation and assembly is as easy as a snap and a twist. No special tools are required to couple or uncouple each belt. Belts can be made to accommodate any length, which makes them ideal for emergency repairs and replacements. Once assembled, V-Link Belts are installed in a fraction of the time needed for endless rubber belts without removing bearings, motors or shafts.

They are suitable in harsh environments and are ideal for metal processing, machine tool, agricultural, packaging, coal and aggregate, pulp and paper, marine, air handling, petrochemical, woodworking, conveying and food industries, HVAC.



Dunlop BTL Ltd

European Distribution Centre
MPT House
Brunswick Road
Cobbs Wood Industrial Estate
Ashford, Kent. UK
TN23 1EL

Contact us

-  +44 (0)1233 663340
-  +44 (0)1233 664440
-  sales@dunlopctl.com
-  www.dunlopctl.com

Manufacturing Facilities

UNITED KINGDOM
FRANCE
GERMANY
ITALY
SPAIN
POLAND
CZECH REPUBLIC
SLOVAKIA
SERBIA
CHINA
USA



TRANSMISSIONS

DUNLOP BTL Ltd, MPT House, Brunswick Road, Cobbs Wood Industrial Estate, Ashford, Kent TN23 1EL, UK
T: +44 (0)1233 663340 • F: +44 (0)1233 664440 • E: sales@dunlopbt.com • W: www.dunlopbt.com

DUNLOP™ and the Flying D device™ are used under licence by DUNLOP BTL Ltd.